



Peak Oil

www.peakoil.co.uk

TECHNICAL DATA

**50% w/w Masterfrost
Automotive &
Industrial Applications**



Peak Oil Ltd

Foxwood Road, Sheepbridge, Chesterfield S41 9RF.

Tel: 01246 450242 Fax: 01246 456017

Email: info@peakoil.co.uk



TECHNICAL DATA

50% w/w Masterfrost

Automotive & Industrial Applications

A pre-diluted 50% Masterfrost solution based on Mono Propylene Glycol, for use in automotive and industrial coolant applications.

Specifically produced to relieve the operator of the problematic area of coolant dilution, where obtaining the correct concentration is critical to the systems performance and protection.

50% w/w Masterfrost will give protection down to -34°C. It contains a highly sophisticated additive package to give enhanced corrosion protection to the coolant system and complies fully to the multi-metal corrosion limits set out in BS 6580 (1992).

Performance Benefits

- ◆ *Superior protection against wear of the cooling system arising from cavitations effects.*
- ◆ *Excellent hard water tolerance, reducing the risks of precipitation leading to cooling system blockage.*

- ◆ *Meets and exceeds the performance requirements of BS 6580 (1992) and most Original Equipment Manufacturer's.*

Corrosion Protection

Glassware tests carried out according to BS5117 standard method. Results show performance exceeding BS6580 (1992).



Batoyle Freedom Group

Lubricants of Excellence

Typical Physical Characteristics

Characteristic	50% w/w Masterfrost
Specific Gravity @ 15°C	1.047

Health and Safety

50% w/w Masterfrost is not known to offer any serious health hazard. We would however, recommend good standards of industrial hygiene are observed when handling this product.

Storage

Drums should be stored on their sides in a clean, dry place and protected from extremes of temperature, store >5°C.

The information given is correct to the best of our knowledge. It is offered in good faith but without guarantee as the conditions and methods of use of our products are beyond our control.