



# Peak Oil

[www.peakoil.co.uk](http://www.peakoil.co.uk)

## TECHNICAL DATA

### Cronus Range Spindle & Circulatory Fluids



**Peak Oil**

**Peak Oil Ltd**

Foxwood Road, Sheepbridge, Chesterfield S41 9RF.

Tel: 01246 450242 Fax: 01246 456017

Email: [info@peakoil.co.uk](mailto:info@peakoil.co.uk)



## **TECHNICAL DATA**

### **Cronus Range**

#### **Spindle & Circulatory Fluids**

A range of high quality lubricating oils manufactured from selected high viscosity index solvent refined mineral base stocks.

The scope of general purpose lubricants is designed to provide efficient and economical lubrication of total or partial loss systems.

Developed for use on machine tools that could include circulating systems, high speed spindles and bearings, certain non-critical hydraulic systems and including other general purpose applications where oil and/or contamination are unavoidable.

#### **Performance Benefits**

- ◆ *Long lubricant life provided by good chemical stability and freedom from deposit formation*
- ◆ *Good resistance to foaming reduces cavitations and increases lubricating efficiency*
- ◆ *Long term protection from rust and corrosion on machine parts*
- ◆ *Covers a wide range of applications*

#### **Health and Safety**

The product is mineral oil based and should be handled according to good standards of industrial hygiene. Further detailed information please is available on request

#### **Storage**

Drums should be stored on their sides in a clean dry place and protected from extremes of temperature, store >5°C.



## Batoyle Freedom Group

*Lubricants of Excellence*

### Typical Physical Characteristics

<b>Cronus</b>	<b>3*</b>	<b>5*</b>	<b>10*</b>	<b>15*</b>	<b>22</b>	<b>32*</b>	<b>46*</b>	<b>68*</b>
Specific Gravity @ 15°C	0.834	0.849	0.873	0.866	0.865	0.870	0.878	0.878
Viscosity @ 40°C (cSt)	3.0	5.0	10.0	15.0	22.0	32.0	46.0	68.0
Viscosity @ 100°C (cSt)	-	-	2.40	3.30	4.30	5.40	6.80	8.80
Viscosity Index	-	-	49	75	95	100	100	100
Closed Flash Point °C	105	110	140	160	195	200	205	210
Pour Point °C	-10	-15	-25	-15	-9	-25	-25	-25

**\* Contains Friction modifiers**

The information given is correct to the best of our knowledge. It is offered in good faith but without guarantee as the conditions and methods of use of our products are beyond our control.