



Peak Oil

www.peakoil.co.uk

TECHNICAL DATA

Diesel Master S 5w/30 Fully Synthetic Diesel Engine Oil



Peak Oil

Peak Oil Ltd

Foxwood Road, Sheepbridge, Chesterfield S41 9RF.

Tel: 01246 450242 Fax: 01246 456017

Email: info@peakoil.co.uk



TECHNICAL DATA

Diesel Master S 5w/30

Fully Synthetic Diesel Engine Oil

The ultimate in synthetic fluid technology, developed to produce an Ultra High Performance Diesel engine oil. It exceeds the very latest European specifications and meets the increasing market demand for fuel-efficient oils.

Designed to give outstanding performance in all heavy duty, highly rated, turbocharged 4 stroke diesel engines operating under the severest of conditions and particularly suited for use in DaimlerChrysler and MAN Euro II engines.

Performance Benefits

- ◆ *Provides outstanding wear protection under the severest of operating conditions, especially effective in the prevention of bore polish, giving extended engine life*
- ◆ *Inherently low viscosity offers exceptional engine efficiencies that can lead to savings of up to 3% on fuel consumption, without compromising on engine protection or increasing oil consumption.*
- ◆ *Excellent protection against oil thickening and 'Black Sludge' formation dramatically reduces operational problems and costly repairs and downtime.*

- ◆ *Exceptional shear stability, maintaining the viscosity of the oil throughout its service life, reducing oil consumption and giving extended wear protection.*
- ◆ *Superior extreme temperature performance gives greatly improved engine protection under critical cold start and high speed, high load conditions, ensuring less wear on batteries, starter motors and engine.*

Performance Specifications

ACEA:	E4, E3
API:	CF
CCMC:	D5
DAF:	ACEA E3
Mercedes-Benz:	228.5
MAN:	M 3277
MTU:	Type 3
Volvo:	VDS-2
RVI:	RLD



Batoyle Freedom Group

Lubricants of Excellence

Typical Physical Characteristics

Characteristic	Diesel Master S 5w/30
Specific Gravity @ 15°C	0.867
Kinematic Viscosity @ 40°C (cSt)	68.3
Kinematic Viscosity @ 100°C (cSt)	11.6
Viscosity Index	165
Pour Point °C	-45
Flash Point (COC) °C	230

Health and Safety

The product is synthetic based and should be handled according to good standards of industrial hygiene. Further detailed information please is available on request.

Storage

Drums should be stored on their sides in a clean dry place and protected from extremes of temperature, store >5°C.

The information given is correct to the best of our knowledge. It is offered in good faith but without guarantee as the conditions and methods of use of our products are beyond our control.