



Peak Oil

www.peakoil.co.uk

TECHNICAL DATA

Ploughmaster Multipurpose Tractor Oil



Peak Oil

Peak Oil Ltd

Foxwood Road, Sheepbridge, Chesterfield S41 9RF.

Tel: 01246 450242 Fax: 01246 456017

Email: info@peakoil.co.uk



TECHNICAL DATA

Ploughmaster

Multipurpose Tractor Oil

Multipurpose Super Universal Tractor Oil specifically developed to meet the severe demands of the agricultural community, providing quality lubrication for the modern tractors, combines and other associated equipment.

Sophisticated technology offers a single lubricant the capability to lubricate 4 stroke turbocharged and naturally aspirated diesel engines, together with transmission systems, including those with inboard wet brakes and oil immersed power take-off clutches, integral hydraulic systems and rear axles. Ploughmaster may also be used on 4 stroke petrol engines of tractors where the performance level of up to API SE is required.

Performance Benefits

- ◆ *Shear stable multi-grading for improved performance in both summer and winter. Providing good cold starting characteristics, coupled with excellent lubrication protection at high operating temperatures*
- ◆ *Reduces operating cost by providing cleaner and more efficient engines, coupled with reduction of wear, therefore providing longer engine life*

- ◆ *Incorporating highly effective friction modifying properties to enable smooth and efficient functioning of wet brake and clutch systems to alleviate chatter*
- ◆ *Simplifies maintenance and servicing by providing one single lubricant to cover most requirements of farm and agricultural equipment*
- ◆ *Provides high standard of performance, together with good fluidity at low temperatures for accurate and reliable hydraulic operations*

The information given is correct to the best of our knowledge. It is offered in good faith but without guarantee as the conditions and methods of use of our products are beyond our control.



Typical Physical Characteristics

Characteristic	Ploughmaster
Specific Gravity @ 15°C	0.892
Kinematic Viscosity @ 40°C (cSt)	83.10
Kinematic Viscosity @ 100°C (cSt)	10.50
Viscosity Index	110
Closed Flash Point °C	205
SAE Rating	15w/30

Performance Specifications

API	CD / SE
API	GL-4
US Military	MIL-L-2104D
Ford	M2C-159B
Massey Ferguson	MF1135 / 1139
Caterpillar	TO-2

Health and Safety

The product is mineral oil based and should be handled according to good standards of industrial hygiene. Further detailed information please is available on request.

Storage

Drums should be stored on their sides in a clean dry place and protected from extremes of temperature, store >5°C.