



Peak Oil

www.peakoil.co.uk

TECHNICAL DATA

Releasol CW1

Concrete Mould Release Oil



Peak Oil

Peak Oil Ltd

Foxwood Road, Sheepbridge, Chesterfield S41 9RF.

Tel: 01246 450242 Fax: 01246 456017

Email: info@peakoil.co.uk



TECHNICAL DATA

Releasol CW1

Concrete Mould Release Oil

Releasol CW1 is premium quality concrete mould release oil containing low odour hydrocarbon solvent, mineral oil and fatty release additives. It has been especially developed for use as a multi-purpose release agent for use on steel or wood.

It is a low viscosity fluid which dries back to a tenacious oily film on the mould surface. It is a superior release agent preventing concrete clinging to the moulds, and provides a high quality surface finish to the concrete.

Releasol CW1 also provides protection for the moulds, keeping them in good condition and free of concrete ready for further use.

- ◆ *Can be used straight from the drum. No mixing required*
- ◆ *Low Odour for better operator acceptance*
- ◆ *Does not contain GAS OIL or PARAFFIN*

Health and Safety

The product is mineral oil based and should be handled according to good standards of industrial hygiene. Further detailed information please is available on request.

Performance Benefits

- ◆ *Multi-purpose mould oil, for use with concrete on steel or wooden moulds*
- ◆ *Provides a smooth surface finish*
- ◆ *Does not cause stains or discolouration*
- ◆ *Low viscosity provides a thorough continuous coating including less accessible areas*

Storage

Drums should be stored on their sides in a clean dry place and protected from extremes of temperature, store >5°C.



Batoyle Freedom Group

Lubricants of Excellence

Typical Physical Characteristics

Characteristic	Releasol CW1
Specific Gravity @ 15°C	0.867
Kinematic Viscosity @ 40°C (cSt)	6.40
Closed Flash Point °C	68

The information given is correct to the best of our knowledge. It is offered in good faith but without guarantee as the conditions and methods of use of our products are beyond our control.