



# Peak Oil

[www.peakoil.co.uk](http://www.peakoil.co.uk)

## TECHNICAL DATA

**Synactra 15w/40**

**X-tra High Performance**

**Semi Synthetic Diesel Engine Oil**



**Peak Oil**

**Peak Oil Ltd**

Foxwood Road, Sheepbridge, Chesterfield S41 9RF.

Tel: 01246 450242 Fax: 01246 456017

Email: [info@peakoil.co.uk](mailto:info@peakoil.co.uk)



## TECHNICAL DATA

### Synactra 15w/40

#### X-tra High Performance Semi Synthetic Diesel Engine Oil

Synactra 15W/40 offers the ultimate performance in terms of the lubrication of heavy duty diesel engines.

Its semi synthetic base and extremely high performance additive content offers outstanding benefits in terms of lubrication, thermal stability, low volatility and low temperature flow characteristics.

In addition to the range of benefits listed, it exceeds the highest performance specifications laid down by both the major OEMs and European and American specification issuing bodies and is specifically recommended for low emission EURO IV & EURO V engines running under very severe conditions.

- ◆ *Gives extended oil change capabilities in line with major OEM recommendations*
- ◆ *Superior extreme temperature performance offers greatly improved engine protection under crucial cold start and high speed, high load conditions*
- ◆ *Shear stable multi grading gives excellent stay in grade capability offering tremendous energy conserving characteristics and fuel efficiency compared to traditional 15W/40 non synthetic grades*

#### Performance Benefits

- ◆ *Formulated using high ratios of synthetic base stocks*
- ◆ *Exceptional antiwear performance dramatically reduces mechanical wear problems under all conditions*
- ◆ *Excellent thermal stability and oxidation control for protection against oil thickening and 'black sludge' formation*

The information given is correct to the best of our knowledge. It is offered in good faith but without guarantee as the conditions and methods of use of our products are beyond our control.



## Typical Physical Characteristics

Characteristic	Synactra 15w/40
Specific Gravity @ 15°C	0.882
Kinematic Viscosity @ 40°C (cSt)	108.90
Kinematic Viscosity @ 100°C (cSt)	14.53
Viscosity Index	136
Closed Flash Point °C	220

## Performance Specifications

API	CF
ACEA	E4-98, E7-04
Daimler Benz	DB228.5
MAN	M3277
Mack	EO - L
Volvo	VDS3, VDS2
Scania	LDF
MTU	Type 3
RVI	RXD

## Health and Safety

The product is synthetic based and should be handled according to good standards of industrial hygiene. Further detailed information please is available on request.

## Storage

Drums should be stored on their sides in a clean dry place and protected from extremes of temperature, store >5°C.