



Peak Oil

www.peakoil.co.uk

TECHNICAL DATA

Tactu Range

Tenacious Circulatory Fluids



Peak Oil

Peak Oil Ltd

Foxwood Road, Sheepbridge, Chesterfield S41 9RF.

Tel: 01246 450242 Fax: 01246 456017

Email: info@peakoil.co.uk



TECHNICAL DATA

Tactu Range

Tenacious Circulatory Fluids

These grades are formulated from highly refined paraffinic mineral oils fortified with selected additives to impart high film strength and anti-fling characteristics.

Specifically recommended where the non-drip, anti-fling characteristics of the additives are required to ensure correct lubrication without excess oil loss. Typical applications may include chain saw and textile machinery lubricants in addition to certain open gear and wire rope applications.

Performance Benefits

- ◆ *High film strength and adhesive characteristics make it ideal for splash-lubricated applications*
- ◆ *Excellent retention on bearings and gears therefore minimising drainage from vertical surfaces*
- ◆ *Long lasting dressing and lubricant for wire ropes and open gears maximising against corrosion and staining*

- ◆ *Beneficial on slow running bearings where a tenacious oil film is preferred*

Health and Safety

The product is mineral oil based and should be handled according to good standards of industrial hygiene. Further detailed information please is available on request

Storage

Drums should be stored on their sides in a clean dry place and protected from extremes of temperature, store >5°C



Typical Physical Characteristics

Tactu	32	46	46AW	68	100
Specific Gravity @ 15°C	0.876	0.880	0.881	0.883	0.887
Viscosity @ 40°C (cSt)	33.20	46.90	47.80	69.70	110.90
Viscosity @ 100°C (cSt)	5.57	7.12	7.12	9.47	12.30
Viscosity Index	104	106	106	101	100
Closed Flash Point °C	203	206	207	214	225

Tactu	150	SL150	220	320	1000
Specific Gravity @ 15°C	0.888	0.893	0.893	0.897	0.925
Viscosity @ 40°C (cSt)	153.60	152.40	226.30	317.80	936.10
Viscosity @ 100°C (cSt)	15.50	16.70	19.90	26.60	46.10
Viscosity Index	101	117	99	108	91
Closed Flash Point °C	225	225	225	225	279

The information given is correct to the best of our knowledge. It is offered in good faith but without guarantee as the conditions and methods of use of our products are beyond our control.